



## Wind resistance classification related to new pricelist 2017

according to ČSN EN 13659 +A1 standard

Class	Pressure nominal	Allowable load	Wind speed (km/h)
class 0	<= 50 Pa	-	< 30
class 1	50 Pa	75 Pa	> 30
class 2	70 Pa	105 Pa	> 35
class 3	100 Pa	150 Pa	> 45
class 4	170 Pa	255 Pa	> 60
class 5	270 Pa	405 Pa	> 75
class 6	400 Pa	600 Pa	> 90

### Wind resistance levels for external blinds with guiding profiles

External blind type	Blind size				
	width: 0 - 2000 mm	width: 2001 - 3000 mm	width: 3001 - 4000 mm	width: 4 001 - 4 500 mm	width: 4 501 - 5000 mm
S90	5	4	3	2	1
Z90	5	4	3	2	1
Z70	5	4	3	2	1
C80	4	3	3	2	1
C65	4	3	2	1	0
F80V	2	1	0	0	0

### Wind resistance level for external blinds with string or string/guiding rail combination

External blind type	Blind size				
	width: 0 - 2 000 mm	width: 2 001 - 3 500 mm	width: 0 - 2 000 mm	width: 2 001 - 3 500 mm	width: 3 501 - 4 000 mm
	height: 0 - 2 500 mm		height: 2 501 - 4 000 mm		
Z90VS	2	1	1	0	0
Z90S	2	1	1	0	0
Z70S	2	1	1	0	0
Z70VS	2	1	1	0	0
C80S	2	1	1	0	0
C80VS	2	1	1	0	0
C65S	2	1	1	0	0
F80	1	0	0	0	0
E50M	1	0	0	0	0
E50K	1	0	0	0	-

ŽALUZIE NEVA s.r.o. , Háj 370, 798 12 Kralice na Hané, Czech Republic  
 e-mail: nevapv@nevapv.cz, phone.: +420-588 003 550, www.nevapv.cz