

F-80 external blinds



F-80 EXTERNAL BLINDS

F-80 external blinds have a classical, curved C-shape without reinforced edges.

The slats with their flat shape form a thin stack after being raised and do not take up much room. They have good shading results.


MAIN ADVANTAGES

- » good shading results
- » thin packet of slats after raising the blind
- » optional tilting on both sides
- » optional operation (crank handle/ motor)
- » slat guide options (string/guiding rail) available


More information at www.nevapv.com




Metal ladder connection
made of stainless steel significantly increases lifetime of external blinds.



Upper profile
in two finishes (extruded aluminium or galvanized steel) is opened downwards:
» allows free access to all components,
» prevents sticking of dirt and other obstacles,
» allows easy adjusting, eg. of gearbox.



Guiding stainless steel string
PVC cover of wire increases lifetime and resistance of external blind. The wire is tensed with a spring and a tension screw.




Quality lift tape
In our production we use lift tape 8 mm of swiss production, this is the highest quality component available in European market.

Rounded hole for lift tape
prevents damage of lift tape during whole lifetime of external blinds.

Components color matching
(ladder, lift tape, guiding pin)
» for light shades grey components are used
» for dark shades black components are used

STANDARD SLAT COLORS



Standard colors on stock, other colors upon request.

BASIC TECHNICAL PARAMETERS

control type	minimum width	maximum area
crank	400 mm	9 m ²
motor	600 mm	16 m ²
Max. width of blind		4000 mm
Max. height of blind		4000 mm
Max. width of connected blinds		8 m (motor-operated)